

**G:B:D:**



**:GECO LUX**

**AUTOMATED FOR  
OVERHEAD AND  
SECTIONAL DOORS**





# ● GECO LUX

## Automated drive unit for overhead and sectional doors

Designed for easy installation on sectional or overhead doors, this automated device allows achieving high movement speed with deceleration during opening and closing.

40W courtesy light incorporated and electronically controllable anti-crushing safety device to achieve a high level of safety as required by the EN 12453 standards.

The unlocking device for emergency manoeuvres is incorporated and can be connected to the door handle.

The optional battery kit allows opening and closing the door even in the event of a blackout.

Technical data	GECO60	GECO80
use	residential	residential
frequency of use	30%	30%
motor power supply	● 24 Vdc	● 24 Vdc
power absorbed	80W	80W
degree of protection	IP40	IP40
maximum thrust	600 N	800 N
nominal thrust	500 N	700 N
thrust regulation	electronic	electronic
door width	3.5 m	4.5 m
door height	2.4 m	2.4 m
operating temperature	-10°C +55°C	-10°C +55°C
maximum stroke	2,800 mm	2,800 mm
built-in courtesy light	YES - 40W	YES - 40W
automatic closing	YES	YES
maximum speed	16 mm/s	12 mm/s
deceleration functions	YES	YES
operator weight	19.1 Kg	19.1 Kg

Accessories



 a **BANDINI INDUSTRIE** company



Associated

---



# GIBIDI

**GI.BI.DI. S.r.l.**

Via Abetone Brennero, 177/B  
46025 Poggio Rusco (MN) - ITALY  
Tel. +39.0386.52.20.11  
Fax +39.0386.52.20.31  
info@gibidi.com

[www.gibidi.com](http://www.gibidi.com)