

G:B:D:



• MODO600-800

**HYDRAULIC
BARRIERS**





● MODO 600 - 800

Hydraulic barriers

Hydraulic barriers for any residential or condominium use with aluminium booms up to 6 metres.
Absolutely silent operation.
Cabinet treated with cataphoresis, painted with powder paints and fired in a kiln at 180°C.

BA100 control unit incorporated, selectable deceleration during opening and closing and option to connect sensitive edges to easily meet the EN 12453 standards.
Ready for installation: balancing adjustment done at the factory.

Technical data	MODO600	MODO800
use	residential	heavy
frequency of use	30%	50%
motor power supply	● 230 Vac - 50/60 Hz	● 230 Vac - 50/60 Hz
power absorbed	190W	200W
degree of protection	IP55	IP55
operating temperature	-20°C +60°C	-20°C +60°C
thermal switch	100°C	100°C
opening time	7 s	7 s
torque regulation	hydraulic	hydraulic
rod length	4.50/6.00 m	4.50/6.00 m
operator weight	53 Kg	55 Kg

Accessories



Opening and closing
limit switches

Heat-treated
steel jack

Unlocking device and force
regulating valves

Adjustable balancing compression
spring for 4.5 or 6 metre rods
6 metres

Control unit incorporated
and prewired in IP55 case

Opening and closing
limit switches



 a **BANDINI INDUSTRIE** company



Associated



GIBIDI

GI.BI.DI. S.r.l.

Via Abetone Brennero, 177/B
46025 Poggio Rusco (MN) - ITALY
Tel. +39.0386.52.20.11
Fax +39.0386.52.20.31
info@gibidi.com

www.gibidi.com