



# MODEL:

## 1. SPECIFICATIONS

STANDARD VOLTAGE:

- ① 12VDC 1Amp.
  - ② RED → POSITIVE(+)
  - ③ BLACK → GROUND(-)
  - ④ ORANGE → BUTTON
  - ⑤ REVERSE POLARITY PROTECTION
- CONTINUOUS DUTY  
START 950mA, STANDBY 100mA.  
STANDARD ON ALL MODELS.  
ADJUSTABLE (FROM 0 TO 9 SECONDS).  
LOCKED WHEN ENERGIZED (POWER TO LOCKED FAIL UNLOCKED).  
16mm DIA. STAINLESS STEEL 16mm THROW.  
SIZE 207mmL x 36mmW (A 42mm Backset minimum must be present).  
SIZE 215mmL x 42mmW x 0.8mmD.  
SIZE 205mmL x 35mmW x 3mmD.  
SIZE 90mmL x 25mmW x 2mmD.  
2PC. EXT. PLATE.  
4PC. M4 x 20 LONG SCREWS.  
4PC. M5 x 11 LONG SCREWS.

SOLENOID:

CURRENT:

AUTOMATIC DEADBOLT:

AUTO RELOCK JUMPER:

FAIL SAFE:

BOLT:

CUTOUT:

COVER PLATE:

FACE PLATE:

STRIKE:

MOUNTING HARDWARE:

WEIGHT:

## 2. OPTIONS

SIGNAL:

DOOR STATUS SENSOR: INDICATES DOOR OPEN OR CLOSED.

YELLOW: NORMALLY OPEN

GREEN: COMMON

SWITCH DATA: SPDT 1.0amp. 30V AC/DC.

SPDT 0.5amp. 30V AC/DC (MAGNETIC PEED SWITCH).