

Product description

Model with basic equipment. Also useable as a heavy-duty electric strike.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 4 mm
- 12-24 Volt voltage range for AC and DC operation
- New connection technology, can be replugged
- Resistant to continuous current across the entire voltage range
- All models can be fitted as required (right-hand/left-hand/horizontally)
- Integrated suppressor diode
- Compatible with Model Range 142U
- Preload modes 400N or 800N can be set

Technical data

Adjustable keeper (FF, FaFix®)	Yes
Fail-locked	Yes
TVS diode	Yes
Changeable connection	Yes
Max. pre-load	400 N / 800 N
Break-in resistance	8000 N
Height	79 mm
Width	20 mm
Depth	28 mm
FaFix® adjustment range	4 mm
Latch bolt engaging depth	6 mm
Operating temperature range	-15 °C to +40 °C
Continuous function load cycles	200000
Load cycles for in-plant test	500000
Installation position	Vertical and horizontal
Suitable for fire doors	Yes
Certified in compliance with	EN 14846:2008

Variants that can be ordered

Order number	Description
143-----Q34	Without striking plate, 12/24V AC/DC DIN L
143-----Q35	Without striking plate, 12/24 V AC/DC DIN R

